

OLIVER

AGRO

MANUFACTURER
OF AGRICULTURAL MACHINERY FOR
FUMIGATION AND NURSERIES



Localizer

Metan Sodio Wapam



Localizer

Metan Sodio Wapam



LT LOCALIZER

- Suited for use on soft, sandy soil.
- During passage, the plow-share creates a cavity that guarantees complete, uniform distribution of the product thanks to the application of a stainless steel nozzle that is available in mirror-shape for the spraying of elevated quantities and fan-shape for lower quantities of product distributed.

TECHNICAL FEATURES

Metansodio Wapam Localizer. Zinc-coated frame structured on 02 rows with stainless steel tank, cage-type roller for greater machine stability and pump drive, John Blue 2455 variable displacement pump, drip-proof series, stainless steel transfer pump. Operating instructions compartment, hand-washing fluid tank, operating instructions and CE manual.

MODELS

L.M. RUL. CIS. 270LT - MT 1,50 6
L.M. RUL. CIS. 270LT - MT 1,75 7
L.M. RUL. CIS. 330LT - MT 2,00 8
L.M. RUL. CIS. 330LT - MT 2,25 9
L.M. RUL. CIS. 380LT - MT 2,50 10
L.M. RUL. CIS. 460LT - MT 2,75 11
L.M. RUL. CIS. 460LT - MT 3,00 12
L.M. RUL. CIS. 600LT - MT 3,50 14
L.M. RUL. CIS. 700LT - MT 4,00 16

METAN SODIO WAPAM LOCALIZER

- **NEW CONCEPT:** A simple machine for the sterilization of all types of soil created for the application of nematocides and antifungal treatments.
- **OBJECTIVE:** More respect for the environment and agricultural equilibrium.
- **CHARACTERISTICS:** Suited for use on every type of soil thanks to the availability of two types of localizer blades studied and tested to make work easier by pushing the product deeper to facilitate gas formation, and total, uniform coverage, and promote the sterilization of the area being treated. The machine comes with a rear cage-type roller that serves to maintain working depth constant, compact the soil, and drive the John Blue CDS variable displacement volumetric pump for the dosing of the product. The pump can be set from 0 to 90 l/mp.
- **ACCESSORIES:** For the greater protection of personnel, a hydraulic motor can be applied for the drainage of the tank and the washing of the system that also guarantee better conservation of the machine when out of use. For particularly sandy soils, a rubber-coated Packer roller can be provided instead of the cage-type roller for better soil compacting; for machines with larger dimensions, lateral wheels are normally applied for greater support and stability.
- **OTHER APPLICATIONS:** A NYLON EXTENDER device can be applied for herbicide effect with partial or total coverage whenever mulching must be performed. The enhanced sunlight effect that occurs beneath the nylon increases the efficacy of sterilization while inhibiting the proliferation of infesting plants at the same time. For more complete machine outfitting, a SPRAYING HOSE EXTENDER device can also be applied in order to finish the transplant preparation work entirely with just one single passage.



DUO LOCALIZER

- Suited for use on hard, clayey soil.
- The lower part is composed of two blades that break up the ground and create a cavity for more uniform product distribution through two horizontal slots at the rear.
- The plowshare support was appropriately metallized to guarantee greater resistance against wear and tempered for greater elasticity.

TECHNICAL FEATURES

Metan Sodio Wapam Localizer. Zinc-coated frame structured on two rows with stainless steel tank, cage-type roller for greater machine stability and pump drive, John Blue 2455 variable displacement pump, drip-proof series, stainless steel transfer pump. Operating instructions compartment, hand-washing fluid tank, operating instructions and CE manual.

MODELS

L.M. RUL. CIS. 270LT - MT 1,50 6
L.M. RUL. CIS. 270LT - MT 1,75 7
L.M. RUL. CIS. 330LT - MT 2,00 8
L.M. RUL. CIS. 330LT - MT 2,25 9
L.M. RUL. CIS. 380LT - MT 2,50 10
L.M. RUL. CIS. 460LT - MT 2,75 11
L.M. RUL. CIS. 460LT - MT 3,00 12
L.M. RUL. CIS. 600LT - MT 3,50 14
L.M. RUL. CIS. 700LT - MT 4,00 16

OLIVER
AGRO

OLIVER AGRO S.R.L.

Via Torre 32 - 37056 Engazzà di Salizzone - Verona - ITALY
Tel. +39(0)45.695.4392 - Fax. +39(0)45.695.4408
info@dittaoliver.com - www.dittaoliver.com